

CFIAR 185MF-7 Diesel Air Compressor

Standard Configuration

- Designed For Frequent Road Hauling
- Durable Engine Starter
- With LED Backlit Instrumentation
- Strong Cold Start Capability
- Quick And Easy Maintenance, Including Self-Contained Oil Separation System
- Safety Features Such As Pressure Displays, Emergency Stop
- GHH Head
- SKF Bearings
- Nano Air Filter Element
- Standard Traction



Heavy Duty Steel Base

- 110% Fluid Isolation
- Simple, Easy-To-Use Control Panel

More Economical CF185MF-7

Our team has developed and tested this air compressor. This compressor has the same configuration as other models except that it is equipped with a FAW engine. Compared with the ISUZU 185, it has a greater price advantage and is one of the ideal choices for users who pursue economic benefits.



Options

- Traction, Box Type
- Aftercooler
- Australian Standard Traction

// Product Parameters CF185MF-7

Compressor	
Free Air Delivery (CFM/M3/MIN)	185/5.2
Working Pressure (BAR/PSI)	7/101.5
Sound Level dB (A) @ 1m	78
Air Cleaner	Dry Paper Filter Type
Compressor Oil Capacity	32
Air Outlets	3/4" x 3

Engine	
Engine Model	FAW
Engine Type	4 Cylinder, Direct-Injection
Nominal Power (KW)	41
Fuel Tank (L)	80
Emission	China Stage II

Dimensions	
Weight (KG)	1050
Max Length (MM)	3375
Width (MM)	1610
Height (MM)	1600

Oil Separator-Receiver Tank	
Shell Dia (MM)	250
Shell Length (MM)	784
Max.Working Pressure (MPa)	1.58
Hydraulic Test Pressure (MPa)	2.37

This parameter is subject to actual conditions and is subject to change without prior notice.