

CFAIR 185M-7 Diesel Air Compressor

Standard Configuration

- Designed For Frequent Road Hauling
- Durable Engine Starter
- With LED Backlit Instrumentation
- Strong Cold Start Capability
- Quick And Easy Maintenance, Including Self-Contained Oil Separation System
- Safety Features Such As Pressure Displays, Emergency Stop
- GHH Head
- SKF Bearings
- Nano Air Filter Element
- Standard Traction



Heavy Duty Steel Base

- 110% Fluid Isolation
- Simple, Easy-To-Use Control Panel

Strong Support Perfectly Balanced Compressor

The four-leg support system evenly distributes the weight of the air compressor, which can effectively reduce vibration, improve stability, and extend the life of the equipment. It can enhance safety, prevent tipping, and ensure the safety of operators. It can also adjust the height for easy movement and maintenance. It can adapt to various terrains and ensure the stable operation of the air compressor in complex environments.



Options

- Ball traction
- Fixed, High Pressure, EU-EPA Certified
- CFAIR Standard Traction

// Product Parameters CF185M-7

Compressor	
Free Air Delivery (CFM/M3/MIN)	185/5.2
Working Pressure (BAR/PSI)	7/101.5
Sound Level dB (A) @ 1m	78
Air Cleaner	Dry Paper Filter Type
Compressor Oil Capacity	32
Air Outlets	3/4" x 3

Engine	
Engine Model	ISUZU
Engine Type	4 Cylinder, Direct-Injection
Nominal Power (KW)	41
Fuel Tank (L)	80
Emission	China Stage II

Dimensions	
Weight (KG)	1180
Max Length (MM)	3180
Width (MM)	1600
Height (MM)	1525

Oil Separator-Receiver Tank	
Shell Dia (MM)	250
Shell Length (MM)	784
Max.Working Pressure (MPa)	1.58
Hydraulic Test Pressure (MPa)	2.37

This parameter is subject to actual conditions and is subject to change without prior notice.