

CFAIR 185M-8 Diesel Air Compressor

Standard Configuration

- Designed For Frequent Road Hauling
- Durable Engine Starter
- With LED Backlit Instrumentation
- Strong Cold Start Capability
- Quick And Easy Maintenance, Including Self-Contained Oil Separation System
- Safety Features Such As Pressure Displays, Emergency Stop
- GHH Head
- SKF Bearings
- Nano Air Filter Element
- Standard Traction



Heavy Duty Steel Base

- 110% Fluid Isolation
- Simple, Easy-To-Use Control Panel

Higher Pressure 185cfm Option

In some special applications, higher pressure is required but the exhaust volume does not need to be very high. Our team has developed an 8bar 185cfm air compressor for this situation. This compressor is undoubtedly one of the most cost-effective choices.



Options

- Traction, Box Type
- Aftercooler
- Australian Standard Traction

// Product Parameters CF185M-8

Compressor	
Free Air Delivery (CFM/M3/MIN)	185/5.2
Working Pressure (BAR/PSI)	8/116
Sound Level dB (A) @ 1m	78
Air Cleaner	Dry Paper Filter Type
Compressor Oil Capacity	32
Air Outlets	3/4" x 3

Engine	
Engine Model	ISUZU
Engine Type	4 Cylinder, Direct-Injection
Nominal Power (KW)	41
Fuel Tank (L)	80
Emission	China Stage II

Dimensions	
Weight (KG)	1030
Max Length (MM)	3375
Width (MM)	1610
Height (MM)	1600

Oil Separator-Receiver Tank	
Shell Dia (MM)	250
Shell Length (MM)	784
Max. Working Pressure (MPa)	1.58
Hydraulic Test Pressure (MPa)	2.37

This parameter is subject to actual conditions and is subject to change without prior notice.